

TEFC - Totally Enclosed Fan Cooled Motors

TECHNICAL DATA

ТИП	FRAME	Pn		N, rpm	M, N.m			I, A		eff. %			PF, %	Nema Code Letter	Weight lbs
		kW	HP		Mn	Ms	Mmax	In	Is	100%	75%	50%	100%		
3600 min-1														2p=2	
33-125-A2	143C	0.75	1.00	3480	2.1	4.5	5.2	1.4	13.9	80.0	81.2	73.0	84.1	M	
33-125-B2	143C	1.10	1.50	3480	3.0	6.9	7.5	2.1	20.1	84.2	82.2	78.6	78.2	M	
33-135-A2	145C	1.50	2.00	3490	4.1	19.8	22.4	2.6	26.8	85.6	84.3	83.3	84.6916	M	32.0
33-135-B2	145C	2.20	3.00	3490	6.0	27.1	31.8	3.6	37.9	85.9	85.9	84.0	89.397	M	
33-170-A2	184C	2.20	3.00	3520	6.0	14.9	24.8	3.6	33.1	86.5	85.5	84.0	88.9	K	54.0
33-170-B2	184C	3.70	5.00	3510	10.2	19.1	33.4	5.9	48.5	88.5	88.0	86.5	89.1	J	63.9
33-170-C2	184C	5.50	7.50	3520	14.9	31.5	54.6	8.3	73.2	89.5	89.5	89.0	93.1	J	
33-200A2	213C	5.5	7.5	3520	15.0	37.3	44.7	8.6	93	89.5	89.0	88.6	89.8	L	92.6
33-200B2	215C	7.5	10.0	3520	20.4	61.0	71.2	11.4	110	90.5	90.3	88.6	91.3	N	104.7
1800 min-1														2p=4	
33-125-A4	143C	0.37	0.50	1725	2.0	5.0	6.0	1.0	5.3	71.8	70.0	60.0	64.8	M	23.5
33-125-B4	143C	0.55	0.75	1725	3.0	7.4	8.9								
33-125-C4	143C	0.75	1.00	1725	5.0	12.5	15.3	1.8	13.8	79.7	78	73.4	65.7	M	32.0
33-135-A4	145C	1.10	1.50	1730	6.1	18.2	22.5	2.1	14.5	84.5	83.6	80.4	77.8956	J	35.3
33-135-B4	145C	1.50	2.00	1730	8.3	24.2	29.1	2.8	18.8	84.6	83.5	82.1	79.5718	J	37.5
33-170-A4	184C	2.20	3.00	1750	12.0	33.8	49.0	3.9	34.0	88.3	88.0	87.5	80.4	K	61.7
33-170-B4	184C	3.70	5.00	1740	20.5	49.5	68.6	6.1	45.2	89.2	88.5	88.2	85.5	J	77.2
33-200A4	213C	5.5	7.5	1750	29.9	52.4	88.6	9.1	58.4	90.3	90.6	89.7	84.1	K	123.0
33-200B4	215C	7.5	10.0	1750	40.9	101.0	136.0	11.9	91.0	91.5	91.3	89.9	86.6	L	145.2