

АСИНХРОННИ ЕЛЕКТРОДВИГАТЕЛИ ЗА ЗАДВИЖВАНЕ НА ЦИРКУЛЯРНИ ДИСКОВЕ**INDUCTION MOTORS FOR CIRCULAR DISCS****ASYNCHRONMOTOREN FÜR HOLZBEARBEITUNGSMASCHINEN****ТРИФАЗНИ ЕЛЕКТРОДВИГАТЕЛИ, THREE-PHASE MOTORS, DREHSTROM MOTOREN**

ТИП TYPE TYP	Мощност Rated output Bemessungsleistung		Напрежение Voltage Spannung	Номинални данни Parameters at Rated Output Betriebswerte bei Bemessungsleistung			Пускови характеристики Starting characteristics Anlaufverhalten			Маса Weight Gewicht
	P1			U	n _N	I _N	cos φ	I _S	M _S	M _{MAX}
	kW	hp	V	min ⁻¹	A		A	N.m	N.m	
3000min ⁻¹										
A90LL-2KS	5.5	7.5	230/400	2900	15.7/9.0	0.88	94/54	21	28.4	25
A90LX-2KSL	5.5	7.5	230/400	2800	15.0/8.6	0.93	90/52	30	35	29.5
A90LX-2KSLB										34
A100LK-2KS	5.5	7.5	230/400	2820	16.9/9.7	0.82	101/58	30	35	29
1500min ⁻¹										
A90LL-4KSR	4.0	5.5	230/400	1250	11.0/6.3	0.92	66/38	40	43	26.5
A100LK-4KSR	4.0	5.5	230/400	1350	11.5/6.6	0.88	70/40	30	34	31
A100L-4KSR	5.5	7.5	230/400	1350	16.0/9.3	0.86	97/56	52	58	35.5
A100LX-4KSR	8.0	10.7	230/400	1350	23.7/13.6	0.85	143/82	70	78	40
A112M-4KSR	5.0	7.0	400/690	1420	8.5/4.9	0.86	51/29	50	60	41
A112MC-4KSR	10.0	13.5	400/690	1340	17.0/9.8	0.85	103/59	75	100	45