

МОТОРИ ЗА ХИДРАВЛИЧНИ СТАНЦИИ
MOTORS FOR HYRAULIC STATIONS
MOTOREN FÜR HYDRAULISCHE STATIONEN

ТИП TYPE TYP	ТЕХНИЧЕСКИ ДАННИ TECHNICAL DATA TECHNISCHE DATEN								400V, 50Hz	
	P _N		n _N	n _B	I _N	I _S	M _S	M _N	M _B	M _{MAX}
	kW	hP	min ⁻¹	min ⁻¹	A	A	N.m	N.m	N.m	N.m
3000min ⁻¹										
AT 80 AA2H	0.75	1.00	2700	2600	3.3	12	6.4	2.7	3.4	7.6
AT 80 AB2H	1.10	1.50	2740	2600	4.2	19	9.2	3.8	5.0	11.0
AT 80 AC2H	1.50	2.00	2750	2600	5.5	27	12.5	5.2	6.8	15.0
AT 80 BA2H	2.20	3.00	2750	2600	7.3	34	18.3	7.6	9.9	22.0
AT 80 BB2H	3.00	4.00	2750	2600	9.0	45	25.0	10.4	13.5	30.0
AT 90 LB2H	4.00	5.50	2750	2600	12.0	60	33.3	13.9	18.1	40.0
AT 90 LX2H	5.50	7.50	2800	2600	16.5	83	45.0	18.8	24.4	54.0
AT 112 MB2	7.50	10.00	2800	2600	22.5	113	61.4	25.6	33.3	73.7
AT 112 MC2	11.00	15.00	2800	2600	33.0	165	90.0	37.5	48.8	108.1
AT 112 MX2	15.00	20.00	2800	2600	45.0	225	122.8	51.2	66.5	147.3
1500min ⁻¹										
AT 80 AA4H	0.55	0.75	1350	1250	2.3	8	12.0	3.9	5.1	13.1
AT 80 AB4H	0.75	1.00	1340	1250	3.0	11	18.0	5.3	6.9	19.3
AT 80 AC4H	1.10	1.50	1360	1250	4.1	17	29.0	7.7	10.0	31.0
AT 80 BA4H	1.50	3.00	1350	1250	5.5	22	38.0	10.6	13.8	42.0
AT 80 BB4H	2.20	3.00	1370	1250	6.1	25	46.0	15.3	19.9	52.9
AT 90 L4H	2.20	3.00	1370	1250	6.1	25	48.0	15.3	19.9	55.2
AT 90 LB4H	3.00	4.00	1370	1250	8.4	33	52.0	20.9	27.2	59.8
AT 90 LX4H	4.00	5.50	1370	1250	11.1	45	61.3	27.9	36.2	70.5
AT 112 MA4	4.00	5.50	1400	1250	11.1	45	60.0	27.3	35.5	69.0
AT 112 MB4	5.50	7.50	1400	1250	15.3	61	82.5	37.5	48.8	95.0
AT 112 MC4	7.50	10.00	1400	1250	20.9	84	112.6	51.2	66.5	129.4
AT 112 MX4	11.00	15.00	1400	1250	30.7	123	165.1	75.0	97.5	189.8