

# ЕЛЕКТРОДВИГАТЕЛИ ЗА ЗДВИЖВАНЕ НА ЕЛЕКТРОТЕЛФЕРИ THREE-PHASE MOTORS FOR ELECTRIC HOISTS DREHSTROMMOTOREN FÜR ELEKTRISCHE HEBEZÜGE

ЕДНОСКОРОСТНИ ДВИГАТЕЛИ, THREE-PHASE ELECTRIC MOTORS, DREHSTROMMOTOREN

Мощност Rated Output Bemessungsleistung		Тип Type Typ		Номинални данни 380-400V Parameters at Rated Output Betriebswerte bei Bemessungsleistung		Пускови характеристики Starting Characteristics Als Vielfaches der Betriebswerte						Maca Weight Gewicht
						Обороти Rotations Upm	Ток Current Strom	Пусков ток Starting Current Anlaufstrom	Пусков момент Starting Torque Anlaufmoment	Спир.момент Breaking Torque Bremsmoment	О.П.Р Oper.Regime Rel. Einschalt dauer	
kW	HP			min <sup>-1</sup>	A	A	Nm	Nm	%	h <sup>-1</sup>	kg	
0.37	0.50	KK1405-4H		1250	1.5	5.0	7.65	2.35	40	60	15.5	
0.25	0.34	KK1405-6H		870	1.2	3.5	6.3	1.96	40	60	15.5	
0.55	0.75	KK1407-4H		1280	2.1	8.0	11.75	2.94	40	60	18.2	
0.37	0.50	KK1407-6H		860	1.8	4.9	10.8	2.45	40	60	18.2	

ДВУСКОРОСТНИ, TWO-SPEED THREE-PHASE ELECTRIC MOTORS, POLUMSCHALTBARE MOTOREN

Мощност Rated Output Bemessungsleistung				Тип Type Typ		Номинални данни 380-400V Parameters at Rated Output Betriebswerte bei Bemessungsleistung		Пускови характеристики Starting Characteristics Als Vielfaches der Betriebswerte						Maca Weight Gewicht				
								Обороти Rotations Upm		Ток Current Strom		Пусков ток Starting Current Anlaufstrom			Пусков момент Starting Torque Anlaufmoment		Сп.момент Breaking Torque Bremsmoment	О.П.Р Oper.Regime Rel. Einschalt dauer
2p1=12		2p2=4		2p1	2p2	2p1	2p2	2p1	2p2	2p1	2p2	2p1	2p2	h-1	kg			
kW	HP	kW	HP	min <sup>-1</sup>		A		A		Nm		Nm	%					
0.06	0.08	0.18	0.245	KK1405-12/4AH		450	1440	1.4	1.2	1.55	3.4	3.8	3.8	0.9	15	30	180	15.5
0.11	0.13	0.37	0.493	KK1407-12/4AH		400	1340	1.7	1.4	2.2	5.0	6.5	6.5	2.4	15	30	180	18.2
0.11	0.13	0.25	0.335	KK1407-12/6AH		400	860	1.7	1.4	2.2	2.8	6.5	6.5	2.4	15	30	180	18.2